

Product Specification Sheet

Rev. 31-JUL-2023

A20[™] Paint Marker

SPECIFICATIONS

Item #:

10701 Black 10702 Blue 10705 White 10710 Metallic Silver 10711 Pink 10714 Metallic Gold

10706 Yellow 10715 Brown 10703 Green 10707 Orange 10712 Violet 10300 Replacement Tip 10704 Red 10709 Light Green 10713 Light Blue



Scan for website

- Style: Valve Activated
- Tip Type: Reversible 3 mm bullet/5 mm chisel
- Barrel Material: Aluminum
- Fill quantity: 13 ml
- Marking Width: 3 mm (0.018") 5 mm (0.196")
- Dimensions*: 5.63" L x 0.63" Ø (142 x 16 mm) *taken w/ marker capped
- Marking Temp. Range: -50° to 150° Fahrenheit (-45° C to 65° C)
- Dry Time: approx. 20 sec.
- Quantity/ Weight Per Box**: 12 ea./ 0.9 lb. (415 g) **other packaging options available
- Quantity/ Weight Per Case: 144 ea./ 11 lb. (5 kg)
- Directions For Use: Shake vigorously with cap on. Press tip until inked. Replace cap after use

PRODUCT FEATURES

- 30% more paint for large marking jobs.
- Reversible bullet / chisel tip provides more marking options.
- Anti-roll cap with clip is easy to remove and replace.
- Marker fits in U-Holder[™].
- Available with Label Guard[™] Antimicrobial Label Coating.
- Permanent xylene free paint.
- Made in USA.

TYPICAL USES

- General purpose industrial marking for quality assurance, color coding and parts identification.
- Marking of tools, inventory, and work-in-progress.
- Highly visible and permanent on most surfaces such as metals, plastics, wood, glass, ceramics, corrugated cardboard, textiles, etc.

SAFETY INFORMATION

- Read SDS before using (available online at <u>www.umarkers.com</u>).
- Conforms to ASTM D4236.
- Keep out of reach of children. For professional use only.