

MATERIAL SAFETY DATA SHEET

U-MARK, Inc.

Rev. Date: November 15, 2006

PRODUCT NAME: 300P INDUSTRIAL PAINT MARKER – GOLD AND SILVER

1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Product Identifier: 300P Industrial Paint Marker- Gold and Silver

General Use: Marking on Most Surfaces

Product Color: Gold, Silver.

U-Mark, Inc., 102 Iowa Ave., Belleville, IL 62220 USA

24-hour Emergency Phone: Infotrac 1-800-535-5053 (within the USA and Canada), 1-352-323-3500 (International)

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS No.	% by Wt.	Exposure Limits (ppm)	
			OSHA TWA	ACGIH TWA
Mineral Spirits	64742-88-7	40-45	500	100
Xylene	1330-20-7	3-15	100	100
Ethylbenzene	100-41-4	1-5	100	100
High Boiling Aliphatic Hydrocarbon	64742-47-8	1-5	500	100
Aluminum pigment*	7429-90-5	10-15	15mg/m3	10mg/m3
Brass Pigment**				
Copper	7440-50-8	20-25	1mg/m3	1mg/m3
Zinc	7440-66-6	1-5	not established	not estab.

* Silver color only; ** Gold Color only

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Flammable liquid and vapor. May cause eye, skin and respiratory tract irritation. May effect central nervous system. If swallowed, do not induce vomiting. Get immediate medical attention

POTENTIAL HEALTH EFFECTS:

INHALATION: Overexposure may cause headache, dizziness and other central nervous system effects. May irritate the respiratory tract.

EYE CONTACT: May cause irritation, redness, tearing, and blurred vision.

SKIN CONTACT: May cause mild irritation, redness, defatting, and dermatitis.

INGESTION: May cause gastrointestinal irritation, nausea, vomiting, and diarrhea. May be harmful or fatal if swallowed.

CHRONIC: Does not contain materials listed as cancer causative agents by NTP or OSHA. IARC (International Agency for Cancer Research) has classified Ethylbenzene as a possible human carcinogen. Repeated overexposure in animals has caused damage to the liver, kidneys, blood and lungs.

4. FIRST AID MEASURES

INHALATION: Remove to fresh air. If breathing has stopped, apply artificial respiration and call a physician immediately.

EYE CONTACT: Flush with plenty of water and call a physician immediately.

SKIN CONTACT: Wash with soap and water. Remove contaminated clothing and launder before use.

INGESTION: Do not induce vomiting. Call a physician.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES: Flash Point: 92-93° F (33-34°C) Method: SFCC

Flammable Limits: LEL 1% UEL 7% .Auto-ignition Temperature: Not available

HAZARDOUS COMBUSTION PRODUCTS: CO, CO2, unidentified organic compounds.

EXTINGUISHING MEDIA: Alcohol foam, dry chemical, CO2.

FIRE FIGHTING INSTRUCTIONS: Wear self-contained breathing apparatus and full protective clothing when large amounts are involved. Avoid breathing vapors. A stream of water may help to spread fire.

6. ACCIDENTAL RELEASE MEASURES

SPILLS: Remove all ignition sources and put on proper protective equipment. Soak up with an absorbent and place in a well-ventilated area or in a closed container. If dry, the material can be disposed of with normal trash. Liquid should be placed in a covered container and held for incineration following all federal, state and local regulations.

7. HANDLING AND STORAGE

HANDLING: Keep markers capped when not in use. Empty containers will contain flammable vapors.

STORAGE: Store in a cool, well-ventilated area away from heat, sparks, or flames.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

ENGINEERING CONTROLS: General exhaust is usually sufficient to keep vapor levels below the PELs.

RESPIRATORY PROTECTION: Not usually required unless in a confined area. If PELs or TLVs are exceeded, use a NIOSH approved respirator with organic vapor cartridges or canister.

SKIN PROTECTION: Chemical resistant gloves when skin contact is possible.

EYE PROTECTION: Not normally required if used as intended. Wear chemical splash goggles in compliance with OSHA if splashing is possible.

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE: 272 – 404°F (119 – 207°C)

VAPOR PRESSURE: 2.3 mm Hg (20°C)

VAPOR DENSITY: >1

SOLUBILITY IN WATER: 0%

SPECIFIC GRAVITY: ~0.9

ODOR: Hydrocarbon.

VOC: 520-650 g/l

APPEARANCE: Colored, opaque liquid.

% VOLATILE BY VOLUME: 50-65

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Stable.

CONDITIONS TO AVOID: Ignition sources.

INCOMPATIBILITY: Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: CO, unidentified organic compounds.

HAZARDOUS POLYMERIZATION: Will not occur.

11. TOXICOLOGICAL INFORMATION

64742-88-7 Mineral Spirits: Oral LD₅₀ 34.6g/kg (rat); Dermal LD₅₀ 15.4g/kg (rabbit);

64742-47-8 VM&P Naphtha: Oral LC₅₀ 3400 ppm (4H, rat.)

1330-20-7 Xylene: Oral LD₅₀ 4.3g/kg. (Rat); Dermal LD₅₀ 2.0g/kg. (Rabbit.)

100-41-4 Ethylbenzene: Oral LD₅₀ 3.5g/kg. (Rat); Dermal LD₅₀ 17.8g/kg. (Rabbit.)

12. ECOLOGICAL INFORMATION

Prevent spilled material from entering natural waterways.

13. DISPOSAL CONSIDERATIONS

Liquid should be considered D001 Unlisted Hazardous Wastes, Characteristic of Ignitability.

14. TRANSPORT INFORMATION

DOT: Printing Ink, 3, UN1210, PG III, Ltd. Qty.

USA Ground Shipments: Consumer Commodity, ORM-D

15. REGULATORY INFORMATION

EPCRA (SARA) Sec. 313 Reportable Materials: Xylene CAS 1330-20-7, and Ethylbenzene CAS 100-41-4.

California Proposition 65 WARNING: this product contains a chemical known to the State of California to cause cancer (Ethylbenzene.)

16. OTHER INFORMATION

HMIS Hazard Ratings: Health 2, Fire 3, Reactivity 0

NFPA Hazard Ratings: Health 2, Fire 3, Reactivity 0

(4 = extreme, 3 = high, 2 = moderate, 1 = slight, 0 = least.)

Caution!

Information presented herein has been compiled from sources that we believe to be reliable and is accurate to the best of our knowledge and belief but its accuracy is not guaranteed. We have control over the use or storage of our products, therefore we cannot assume any responsibility or liability in connection with the use or inability to use them.. Specifically, our products and MSDS are supplied under the condition that Buyers and Users test our products for their intended use and make their own decision of suitability. Responsibility for compliance with all applicable Federal, State or local laws and regulations concerning the use and dissemination of this MSDS and sale and use of the material described herein rests solely upon the purchaser.