

MATERIAL SAFETY DATA SHEET

U-MARK, Inc.

Revision Date: January 30, 2007

PRODUCT NAME: USI STENCIL INK – BLACK AND WHITE

1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Product Identifier: USI Stencil Ink
General Use: All surface, alcohol-based stencil ink.
Product Color: Black, White

U-Mark, Inc., 102 Iowa Ave., Belleville, IL 62220

24-hour Emergency Phone: Infotrac 1-800-535-5053 (within the USA and Canada), 1-352-323-3500 (International)

2. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	CAS No.	% by Wt.	Exposure Limits (ppm)	
			OSHA TWA	ACGIH TWA
Diacetone Alcohol	123-42-2	40- 70	50	50
Dipropylene glycol methyl ether	34590-94-8	10-20	100	100

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Combustible liquid and vapor. May cause eye and skin irritation.

Overexposure may cause dizziness.

POTENTIAL HEALTH EFFECTS:

INHALATION: Excessive inhalation may cause nasal and respiratory irritation, nausea, headache or dizziness.

EYE CONTACT: May cause irritation, redness, and possible corneal injury.

SKIN CONTACT: Moderate irritation.

INGESTION: May cause nausea, vomiting, abdominal pain, dizziness and unconsciousness. Can cause kidney and liver damage.

CHRONIC: Does not contain a chemical listed as carcinogenic by NTP, IARC, and OSHA. Repeated overexposure may cause liver and blood abnormalities and kidney damage.

4. FIRST AID MEASURES

INHALATION: Remove to fresh air. Get medical attention if breathing is difficult.

EYE CONTACT: Flush with water immediately for 15 minutes. Get medical attention if irritation persists

SKIN CONTACT: Remove contaminated clothing. Wash skin thoroughly with soap and water.

INGESTION: Call a physician immediately. Do not induce vomiting unless directed by medical personnel. Keep person warm.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES:

Flash Point: 141°F (61°C) Method: TCC Flammable Limits: LEL 1.1%, UEL 6.9%

Auto-ignition Temperature: Not available

HAZARDOUS COMBUSTION PRODUCTS: CO, CO₂

EXTINGUISHING MEDIA: Water spray, dry chemical, CO₂, foam.

FIRE FIGHTING INSTRUCTIONS: When large quantities or indoor fires are involved, wear self-contained breathing apparatus and complete protective clothing.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Soak up with absorbent and hold in covered container for incineration according to all Federal, state or provincial and local regulations.

LARGE SPILL: Eliminate ignition sources and put on personal protective equipment. Dike and/or pump into appropriate containers. Destroy by incineration in accordance with applicable regulations.

7. HANDLING AND STORAGE**HANDLING:** Wash thoroughly after handling.**STORAGE:** Store away from heat, sparks, or flames.

8. EXPOSURE CONTROL/PERSONAL PROTECTION**ENGINEERING CONTROLS:** General ventilation is recommended to keep vapors below exposure limits.**RESPIRATORY PROTECTION:** Not usually required unless in confined area. Then use a NIOSH/MSHA approved respirator equipped for organic vapors if exposure limits are exceeded.**SKIN PROTECTION:** Wear impervious gloves if hand contact is anticipated.**EYE PROTECTION:** Chemical splash goggles should be used when working with chemicals.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Range: 335 to 408°F (169 to 209°C)

Melting Point: Not available

Vapor Pressure: 1 mm Hg, 68°F (20°C)

Vapor Density: 4

Solubility in Water: Partial

Specific Gravity: 1.1 to 1.26

Weight/Gallon: 9.2 to 10.5 lbs.

VOC: ~ 900 g/l

Odor: Sweetish

% Volatile by Vol.: ~ 90%

Appearance: Colored, opaque liquid

10. STABILITY AND REACTIVITY**CHEMICAL STABILITY:** (Conditions to avoid) High temperatures.**INCOMPATIBILITY:** Strong oxidizing agents, strong acids and strong alkalis.**HAZARDOUS DECOMPOSITION PRODUCTS:** CO, CO₂**HAZARDOUS POLYMERIZATION:** Will not occur.

11. TOXICOLOGICAL INFORMATIONDiacetone alcohol: LD₅₀ 4g/kg (oral, rat), 13.5g/kg (skin, rabbit); LC₅₀ >1500 ppm (8H, rat). IDLH Level: 2100 ppm. Dipropylene glycol methyl ether: LD₅₀ 5660mg/kg (oral, rat), 9.5g/kg (skin, rat).

12. ECOLOGICAL INFORMATION

Prevent any runoff from reaching natural waterways.

13. DISPOSAL CONSIDERATIONS

See Section 6. Liquid waste materials would be considered Code D001 (Characteristic - Ignitability)

14. TRANSPORT INFORMATION

DOT, IATA, IMO: Printing Ink, 3, UN1210, PG III. No markings required when shipped in USA by ground.

15. REGULATORY INFORMATION

EPCRA (SARA) Sec. 313 Reportable Materials: None

TSCA: All components are included in the TSCA Inventory.

16. OTHER INFORMATION

HMIS Hazard Rating Health 1, Fire 2, Reactivity 0

(4 = extreme, 3= high, 2= moderate, 1= slight, 0 = negligible)

Caution!

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Since conditions of use are beyond our control, we make no warranties, expressed or implied, except those that may be contained in our written contract of sale or acknowledgment. This MSDS is supplied under the condition that all persons receiving it will make their own evaluation as to its suitability for their purposes before using it. Responsibility for compliance with all applicable federal, state or local regulations concerning the use and dissemination of this MSDS and sale and use of the material described herein rests solely upon the purchaser.