

# MATERIAL SAFETY DATA SHEET

**U-MARK, Inc.**

Revision Date: January 30, 2007

**PRODUCT NAME: UZ ALCOHOL-BASED INK JET INK**

## 1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Product Identifier: UZ Alcohol-based Ink Jet Ink

General Use: Jet Printer Ink for all surfaces.

Product Color: Black, Red, Blue, Green

U-Mark, Inc., 102 Iowa Ave., Belleville, IL 62220

**24-hour Emergency Phone: Infotrac 1-800-535-5053 (within the USA and Canada), 1-352-323-3500 (International)**

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	CAS No.	% by Wt.	Exposure Limits (ppm)	
			OSHA TWA	ACGIH TWA
Ethyl Alcohol	64-17-5	75-90	1000	1000
Isopropyl Alcohol	67-63-0	5-10	400	400

## HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW: Flammable liquids and vapor. May cause eye, skin and respiratory tract irritation. Overexposure may cause dizziness or drowsiness.**

### POTENTIAL HEALTH EFFECTS:

**INHALATION:** Excessive inhalation may cause irritation of the nose and respiratory tract and Central Nervous System effects such as headache, dizziness and drowsiness.

**EYE CONTACT:** May cause irritation, redness, tearing, blurred vision.

**SKIN CONTACT:** May cause mild irritation, defatting of the skin and dermatitis.

**INGESTION:** Can cause gastrointestinal irritation, nausea and vomiting, diarrhea, dizziness.

**CHRONIC:** Contains no materials listed as cancer causers by NTP, IARC, or OSHA. Long term overexposure may cause liver damage, anemia, reproductive effects.

## 4. FIRST AID MEASURES

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

**EYE CONTACT:** Immediately flush eyes with plenty of water. Get medical attention if irritation persists.

**SKIN CONTACT:** Wash with soap and water. Remove contaminated clothing.

**INGESTION:** Get medical attention immediately. Do not induce vomiting.

## 5. FIRE FIGHTING MEASURES

### FLAMMABLE PROPERTIES:

Flash Point: 56°F (13°C)

Method: TCC

Flammable Limits: 3.53 to 21.2% vol. in air

**HAZARDOUS COMBUSTION PRODUCTS:** CO, CO<sub>2</sub>.

**EXTINGUISHING MEDIA:** Alcohol foam, dry chemical, CO<sub>2</sub>.

**FIRE FIGHTING INSTRUCTIONS:** Use self-contained breathing apparatus and full protective clothing for large or indoor fires. Use water spray to cool containers.

**6. ACCIDENTAL RELEASE MEASURES**

Remove all ignition sources and ventilate area. Absorb spilled material, and place in a container for disposal (e.g. incineration). Dispose of in accordance with all Federal, state and local regulations

**7. HANDLING AND STORAGE**

**HANDLING:** Wash thoroughly after handling.

**STORAGE:** Store away from heat, sparks, or flames. Lids must be well secured.

**8. EXPOSURE CONTROL/PERSONAL PROTECTION**

**ENGINEERING CONTROLS:** General ventilation is recommended to keep vapors below exposure limits.

**RESPIRATORY PROTECTION:** Use a NIOSH/MSHA approved respirator equipped for organic vapors if exposure limits are exceeded.

**SKIN PROTECTION:** Wear impervious gloves if hand contact is anticipated.

**EYE PROTECTION:** Chemical splash goggles should be used when working with chemicals.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Boiling Range: 173° - 181°F (78° - 83°C)

Vapor Density: 1.6 (air = 1)

Solubility in Water: Complete

Weight/Gallon: 6.6 lbs.

Odor: Alcohol

Melting Point: Not Applicable

Appearance: Black Liquid

Specific Gravity: 0.79

VOC: 900 g/l

% Volatile by Vol.: >99%

**10. STABILITY AND REACTIVITY**

**CHEMICAL STABILITY:** (Conditions to avoid) None

**INCOMPATIBILITY:** Strong oxidizing agents and strong acids.

**HAZARDOUS DECOMPOSITION PRODUCTS:** CO, CO<sub>2</sub>

**HAZARDOUS POLYMERIZATION:** Will not occur.

**11. TOXICOLOGICAL INFORMATION**

Ethyl Alcohol: LD<sub>50</sub> 7.06g/kg (oral, rat); LC<sub>50</sub> 20,000 ppm (10H, rat).

Isopropyl Alcohol: LD<sub>50</sub> 5045mg/kg (oral, rat), 12.8g/kg (skin, rabbit); LC<sub>50</sub> 16,000 ppm (4H, rat).

**12. ECOLOGICAL INFORMATION**

None available on this product.

**13. DISPOSAL CONSIDERATIONS**

See Section 6. Waste materials would be considered Code D001 (Characteristic - Ignitability)

**14. TRANSPORT INFORMATION**

IATA, IMDG, DOT: Printing Ink, 3, UN1210, PG II;

USA Ground (Quarts or less): Consumer Commodity, ORM-D.

**15. REGULATORY INFORMATION**

EPCRA (SARA) Sec. 313 Reportable Materials: None

TSCA: All components are listed in the TSCA Inventory.

**16. OTHER INFORMATION**

HMIS Hazard Ratings: Health 2, Fire 3, Reactivity 0

NFPA Hazard Ratings: Health 2, Fire 3, Reactivity 0

(4 = extreme, 3 = high, 2 = moderate, 1 = slight, 0 = least)

**Caution!**

Information presented herein has been compiled from sources that we believe to be reliable and is accurate to the best of our knowledge and belief but its accuracy is not guaranteed. U-Mark, Inc. has no control over the use or storage of its products, therefore we cannot assume any responsibility or liability in connection with the use- or inability to use them. Please see our Terms and Conditions of Sale, available upon request. Specifically, our products and MSDS are supplied under the condition that Buyers and Users test our products for their intended use and make their own decision of suitability. Responsibility for compliance with all applicable Federal, State or local laws and regulations concerning the use and dissemination of this MSDS and sale and use of the material described herein rests solely upon the purchaser.