

MATERIAL SAFETY DATA SHEET

U-MARK

Revision Date: December 5, 2006

PRODUCT NAME: DOD INK JET SYSTEM INKS AND CONDITIONER

1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Product Identifier: DOD INK JET INK BLACK, RED, GREEN, BLUE AND DOD
CONDITIONER

General Use: Use with Ink Jet Systems on porous surfaces.

Product Color: Black, Red, Green, Blue or Light Blue (Conditioner)

U-Mark, Inc., 102 Iowa Ave., Belleville, IL 62220 USA tel. 618 -235-7500

24-hour Emergency Phone Infotrac: 1-800-535-5053 (USA), 1-352-323-3500 (International)

2. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	CAS No.	% by Wt.	Exposure Limits (ppm) OSHA ACGIH TWA STEL
------------	---------	----------	--

Diethylene Glycol Monobutyl Ether	112-34-5	>29	None established
-----------------------------------	----------	-----	------------------

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: May be harmful if swallowed in large amounts.

POTENTIAL HEALTH EFFECTS:

INHALATION: None expected under normal conditions of use.

EYE CONTACT: May cause slight irritation.

SKIN CONTACT: May cause slight irritation.

INGESTION: Small amounts are unlikely to cause injury.

CHRONIC: Does not contain a material listed as carcinogenic by NTP, IARC, and OSHA. Repeated overexposure may cause liver, kidney and gastrointestinal effects.

4. FIRST AID MEASURES

INHALATION: Remove to fresh air. Get medical attention if breathing is difficult.

EYE CONTACT: Flush with water immediately for 15 minutes. Contact a physician.

SKIN CONTACT: Remove contaminated clothing. Wash skin with soap and flowing water.

INGESTION: Call a physician immediately. Do not induce vomiting. Keep person warm.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES:

Flash Point: > 212°F (> 100°C) Method: PMCC Flammable Limits: Not applicable

HAZARDOUS COMBUSTION PRODUCTS: CO, CO₂, trace organic aldehydes and acids.

EXTINGUISHING MEDIA: Water spray, dry chemical, CO₂, foam.

FIRE FIGHTING INSTRUCTIONS: When large quantities or indoor fires are involved, wear self-contained breathing apparatus and complete protective clothing.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Soak up with absorbent and hold in covered container for incineration according to applicable regulations.

LARGE SPILL: Eliminate ignition sources and put on personal protective equipment. Dike and/or pump into appropriate containers. Destroy by incineration in accordance with all Federal, State and local laws and regulations.

7. HANDLING AND STORAGE

HANDLING: Wash thoroughly after handling.

STORAGE: Store in cool area.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

ENGINEERING CONTROLS: General exhaust is recommended.

RESPIRATORY PROTECTION: Not usually required unless spraying ink in a confined area. Then a NIOSH/MSHA approved respirator with organic vapor cartridges or canister should be used.

SKIN PROTECTION: Wear impervious gloves if hand contact is anticipated.

EYE PROTECTION: Chemical splash goggles should be used when working with chemicals.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Range: >212°F (>100°C)

Melting Point: Not Applicable

Vapor Pressure: < 0.01mm Hg, 68°F (20°C)

Vapor Density: 3.66

Solubility in Water: Complete

Specific Gravity: 1.01

Weight/Gallon: 8.2 lbs

VOC: > 290 g/l

Odor: Mild

% Volatile by Vol.: >29%

Appearance: Colored Liquid

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY (Conditions to avoid): None

INCOMPATIBILITY: Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO₂.

HAZARDOUS POLYMERIZATION: Will not occur.

11. TOXICOLOGICAL INFORMATION

Diethylene Glycol: LD₅₀ 1g/kg (oral, human), 11.89g/kg (skin, rabbit).

12. ECOLOGICAL INFORMATION

Prevent any runoff from reaching natural waterways.

13. DISPOSAL CONSIDERATIONS

See Section 6. Waste materials would be considered non-hazardous

14. TRANSPORT INFORMATION

DOT, IATA, IMDG: Not regulated

15. REGULATORY INFORMATION

EPCRA (SARA) Sec. 313 Reportable Materials: None

TSCA: All components are listed in the TSCA Inventory.

16. OTHER INFORMATION

HMIS and NFPA Rating: Health 1, Flammability 0, Reactivity 0 (4 = extreme, 3 = high, 2 = moderate, 1 = slight, 0 = least).

Caution!

Information presented herein has been compiled from sources that we believe to be reliable and is accurate to the best of our knowledge and belief but its accuracy is not guaranteed. U-Mark, Inc. has no control over the use or storage of our products, therefore we cannot assume any responsibility or liability in connection with the use- or inability to use them. Please see our Terms and Conditions of Sale, available upon request. Specifically, our products and MSDS are supplied under the condition that Buyers and Users test our products for their intended use and make their own decision of suitability. Responsibility for compliance with all applicable Federal, State or local laws and regulations concerning the use and dissemination of this MSDS and sale and use of the material described herein rests solely upon the purchaser.