

A10™ Paint Marker



Scan for website

SPECIFICATIONS

Item #:

10101 Black	10102 Blue	10103 Green	10104 Red
10105 White	10106 Yellow	10107 Orange	10107 Light Green
10110 Metallic Silver	10111 Pink	10112 Violet	10113 Light Blue
10114 Metallic Gold	10115 Brown	10118 Metallic Copper	10300A Replacement Tip

- Style: Valve Activated
- Tip Type: Reversible 2mm bullet/ 4mm chisel
- Barrel Material: Aluminum
- Fill quantity: 10ml
- Marking Width: 2mm (0.078") - 4mm (0,157")
- Dimensions*: 5.69" L x 0.56" Ø (144 x 14 mm.) *taken w/ marker capped
- Marking Temp. Range: -50° to 150° Fahrenheit (-45° C to 65° C)
- Dry Time: approx. 20 sec.
- Quantity/ Weight Per Box**: 12ea./ 0.75 lb. (340g) **other packaging options available
- Quantity/ Weight Per Case: 144ea./ 9 lb. (4.1kg)
- Directions For Use: Shake vigorously with cap on. Press tip until inked. Replace cap after use

PRODUCT FEATURES

- Press-tip valve regulates paint flow and extends marking mileage.
- Heavy duty tip is made to withstand repetitive industrial applications.
- Best value among standard paint markers.
- Marker fits in U-Holder™.
- Available with Label Guard™ Antimicrobial Label Coating.
- Permanent xylene free paint.
- Made in USA.

TYPICAL USES

- General purpose industrial marking for quality assurance, color coding and parts identification.
- Marking of tools, inventory, and work-in-progress.
- Highly visible and permanent on most surfaces such as metals, plastics, wood, glass, ceramics, corrugated cardboard, textiles, etc.

SAFETY INFORMATION

- Read SDS before using (available online at www.umarkers.com).
- Conforms to ASTM D4236.
- Keep out of reach of children. For professional use only.