



Product Specification Sheet

Rev. 2-AUG-2023

100CHP™ Certified High Purity Marker



Scan for website

SPECIFICATIONS

Item #:

10205CHP White 10300A Replacement Tip

- Style: Valve Activated
- Tip Type: Medium Bullet-Chisel
- Barrel Material: Aluminum
- Fill quantity: 10ml
- Marking Width: 2mm (0.078") - 4mm (0.158")
- Dimensions*: 5.69" L x 0.56" Ø (144 x 14 mm) *taken w/ marker capped
- Marking Temp.: -50° to 150° Fahrenheit (-45° C to 65° C)
- Dry Time: approx. 20 sec.
- Quantity/ Weight Per Box**: 12ea./ 0.75 lb. (340 g) **other packaging options available
- Quantity/ Weight Per Case: 144ea./ 9 lb. (4.1 kg)
- Directions For Use: Shake vigorously with cap on. Press tip until inked. Replace cap after use

PRODUCT FEATURES

- Low chlorides, low halogens, and metals in the paint formula prevent corrosion of stainless steel.
- Certified high purity formula meets U. S. Dept. of Energy Specifications of RDT-F7-3.7-5.1.
- Each Lot of paint is individually certified, and the Lot number is printed on each marker label.
Certificate for each Lot is available online at www.umarkers.com/resources/sds.htm
- Xylene-Free paint dries quickly (< 30 sec.) and is weather, UV and abrasion resistant.
- Ideal to mark on stainless steel.
- Marks on metals, glass, plastics and more.
- Made in USA.

TYPICAL USES

- General purpose marking in nuclear, aviation, and defense applications.
- Inspection and Q.C. on stainless steel plates and pipes.
- Welding and Fabrication.

SAFETY INFORMATION

- Read SDS before using (available online at www.umarkers.com).
- Keep out of reach of children. For professional use only.