


100P™ Fine Line



SPECIFICATIONS

- | | | |
|------------|----------------|-------------------------|
| • Item # : | 10201FL Black | 10209FL Bright Green |
| | 10202FL Blue | 10210FL Metallic Silver |
| | 10203FL Green | 10211FL Pink |
| | 10204FL Red | 10212FL Violet |
| | 10205FL White | 10213FL Light Blue |
| | 10206FL Yellow | 10214FL Metallic Gold |
| | 10207FL Orange | 10215FL Brown |
| | | 10200FL Fine Line Tip |



- Style: Valve Activated
- Tip Type: Fine Line
- Marking Width: 1.5mm. (0.059")
- Dimensions: 5.69" L x 0.56" Ø (144 x 14 mm.) *
- Marking Temp. Range: -50° to 150° Fahrenheit (-45° to 65° C)
- Dry Time: approx. 45 sec.
- Quantity/ Weight Per Box: 12ea./ 0.75 lb./ (340 g.)
- Quantity/ Weight Per Case: 144ea./ 9 lb./ (4.1 kg.)
- **Directions For Use:** Shake vigorously with cap on. Press tip until inked. Replace cap after use.

* Dimensions taken w/ marker capped.

PRODUCT FEATURES

- Two available sizes for medium and fine line marking.
- Heavy duty aluminum barrel and air-tight cap withstand industrial use.
- Liquid paint is dispensed by a patented valve to ensure smooth paint flow.
- Paint is UV and weather resistant.
- Marker fits in U-Holder™.

TYPICAL USES

- Marks well on rusty and oily metals, dry or damp wood, glass plastics, rubber tape, cardboard, waxed cartons, ceramics, tiles, concrete, and more.

SAFETY INFORMATION

- Read MSDS before using (available online at www.umarkers.com).
- Keep out of reach of children. For professional use only.

Important Information

The technical information and data provided in this PSS should be considered typical and, should not be used as a specification. Applications may vary, therefore, testing is recommended before use. Our Technical Department will be happy to work with you and help you select the best product for your application.

Rev. 04/13/2020