



Product Specification Sheet

Rev. 14-MAY-2025

100P™ Fine Line



Scan for website

SPECIFICATIONS

Item #:

| | | | |
|-------------------------|----------------|--------------------|----------------|
| 10201FL Black | 10202FL Blue | 10203FL Green | 10204FL Red |
| 10205FL White | 10206FL Yellow | 10207FL Orange | 10210FL Silver |
| 10211FL Pink | 10212FL Violet | 10213FL Light Blue | 10214FL Gold |
| 10200FL Replacement Tip | | | |

- Style: Valve Activated
- Tip Type: Fine Line
- Barrel Material: Aluminum
- Fill quantity: 10 ml
- Marking Width: 1.5 mm (0.059")
- Dimensions*: 5.69" L x 0.56" Ø (144 mm x 14 mm) *taken w/ marker capped
- Marking Temp. Range: -50° to 150° Fahrenheit (-45° C to 65° C)
- Dry Time: approx. 45 sec.
- Quantity/ Weight Per Box*: 12 ea./ 0.75 lb. (340 g) *other packaging options available
- Quantity/ Weight Per Case: 144 ea./ 9 lb. (4.1 kg)
- **Directions For Use:** Shake vigorously with cap on. Press tip until inked. Replace cap after use

PRODUCT FEATURES

- High Performance industrial paint is dispensed through a precision valve to ensure smooth paint flow.
- Heavy duty aluminum barrel and air-tight cap withstand industrial use.
- Oil-based paint has exceptional outdoor durability and UV resistance and adheres to rusty and oily metals.
- Marker fits in U-Holder™.
- Made in USA.

TYPICAL USES

- Marks well on rusty and oily metals, dry or damp wood, glass, plastics, rubber tape, cardboard, waxed cartons, ceramics, tiles, concrete, and more.
- Automotive and steel recyclers, surveyors, auto repair shops.

SAFETY INFORMATION

- Read SDS before using (available online at www.umarkers.com).
- Keep out of reach of children. For professional use only.