



# Product Specification Sheet

Rev. 14-MAY-2025

## 100P™ Industrial Paint Marker



Scan for website

### SPECIFICATIONS

Item #:

10201 Black	10202 Blue	10203 Green	10204 Red
10205 White	10206 Yellow	10207 Orange	10210 Silver
10211 Pink	10212 Violet	10213 Light Blue	10214 Gold
10100 Replacement Tip			

- Style: Valve Activated
- Tip Type: Bullet
- Barrel Material: Aluminum
- Fill quantity: 10 ml
- Marking Width: 2 mm (0.078")
- Dimensions\*: 5.69" L x 0.56" Ø (144 mm x 14 mm) \*taken w/ marker capped
- Marking Temp. Range: -50° to 150° Fahrenheit (-45° C to 65° C)
- Dry Time: approx. 45 sec.
- Quantity/ Weight Per Box\*: 12 ea./ 0.75 lb. (340 g) \*other packaging options available
- Quantity/ Weight Per Case: 144 ea./ 9 lb. (4.1 kg)
- **Directions For Use:** Shake vigorously with cap on. Press tip until inked. Replace cap after use

### PRODUCT FEATURES

- Industrial, oil-based paint has exceptional outdoor durability and UV resistance and adheres to rusty and oily metals.
- Heavy duty aluminum barrel and air-tight cap withstand industrial use.
- High performance industrial paint is dispensed through a precision valve to ensure smooth paint flow.
- Marker fits in U-Holder™.
- Made in USA.

### TYPICAL USES

- Marks on rusty and oily metals, dry or damp wood, glass, plastics, rubber tape, cardboard, waxed cartons, ceramics, tiles, concrete, and more.
- Automotive and steel recyclers, surveyors, auto repair shops.

### SAFETY INFORMATION

- Read SDS before using (available online at [www.umarkers.com](http://www.umarkers.com)).
- Keep out of reach of children. For professional use only.