

A10™ Paint Marker



SPECIFICATIONS

- Item # : 10101 Black 10109 Light Green
 - 10102 Blue 10110 Silver
 - 10103 Green 10111 Pink
 - 10104 Red 10112 Violet
 - 10105 White 10113 Light Blue
 - 10106 Yellow 10114 Gold
 - 10107 Orange 10115 Brown
 - 10109 Light Green 10300A HD Bullet Tip
- *All colors also available in individual Blister packs

- Style: Valve Activated
- Tip Type: Medium Bullet
- Marking Width: 2mm. (0.078")
- Dimensions: 5.69" L x 0.56" Ø (144 x 14 mm.) *
- Marking Temp. Range: -50° to 150° Fahrenheit (-45° to 65° C)
- Dry Time: approx. 20 sec.
- Quantity/ Weight Per Box: 12ea./ 0.75 lb./ (340 g.)
- Quantity/ Weight Per Case: 144ea./ 9 lb./ (4.1 kg.)
- **Directions For Use:** Shake vigorously with cap on. Press tip until inked. Replace cap after use.

* Dimensions taken w/ marker capped.

PRODUCT FEATURES

- Press-tip valve regulates paint flow and extends marking mileage.
- Heavy duty tip is made to withstand repetitive industrial applications.
- Best value among standard paint marker.
- Marker fits in U-Holder™.

TYPICAL USES

- General purpose industrial marking for quality assurance, color coding and parts identification.
- Marking of tools, inventory, and work-in-progress.
- Highly visible and permanent on most surfaces such as metals, plastics, wood, glass, ceramics, corrugated cardboard, textiles, etc.

SAFETY INFORMATION

- Read MSDS before using (available online at www.umarkers.com).
- These markers are certified as non-toxic per ASTM D4236 to contain no ingredients in quantities expected to cause significant or chronic toxicity to consumers. The markers require no precautionary labeling in accordance with the CPSC (Consumer Product Safety Commission) Regulations as mandated by Labeling of Hazardous Materials Act (LHAMA).
- Keep out of reach of children. For professional use only.



Made in USA

Rev. 07/27/2016