

A10™ Paint Marker



SPECIFICATIONS

- Item # : 10101 Black 10110 Metallic Silver
 - 10102 Blue 10111 Pink
 - 10103 Green 10112 Violet
 - 10104 Red 10113 Light Blue
 - 10105 White 10114 Metallic Gold
 - 10106 Yellow 10115 Brown
 - 10107 Orange 10300A HD Bullet Tip
 - 10109 Light Green
- *All colors also available in individual Blister packs

- Style: Valve Activated
- Tip Type: Medium Bullet
- Marking Width: 2mm. (0.078")
- Dimensions: 5.69" L x 0.56" Ø (144 x 14 mm.) *
- Marking Temp. Range: -50° to 150° Fahrenheit (-45° to 65° C)
- Dry Time: approx. 20 sec.
- Quantity/ Weight Per Box: 12ea./ 0.75 lb./ (340 g.)
- Quantity/ Weight Per Case: 144ea./ 9 lb./ (4.1 kg.)
- **Directions For Use:** Shake vigorously with cap on. Press tip until inked. Replace cap after use.

* Dimensions taken w/ marker capped.

PRODUCT FEATURES

- Press-tip valve regulates paint flow and extends marking mileage.
- Heavy duty tip is made to withstand repetitive industrial applications.
- Best value among standard paint marker.
- Marker fits in U-Holder™.

TYPICAL USES

- General purpose industrial marking for quality assurance, color coding and parts identification.
- Marking of tools, inventory, and work-in-progress.
- Highly visible and permanent on most surfaces such as metals, plastics, wood, glass, ceramics, corrugated cardboard, textiles, etc.

SAFETY INFORMATION

- Read MSDS before using (available online at www.umarkers.com).
- These markers are certified as non-toxic per ASTM D4236 to contain no ingredients in quantities expected to cause significant or chronic toxicity to consumers. The markers require no precautionary labeling in accordance with the CPSC (Consumer Product Safety Commission) Regulations as mandated by Labeling of Hazardous Materials Act (LHAMA).
- Keep out of reach of children. For professional use only.



Important Information

The technical information and data provided in this PSS should be considered typical, and should not be used as a specification. Applications may vary therefore testing is recommended before use. Our Technical Department will be happy to work with you and help you select the best product for your application.

