



Product Specification Sheet

Rev. 31-JUL-2023

A20™ Paint Marker



Scan for website

SPECIFICATIONS

Item #:

10701 Black	10702 Blue	10703 Green	10704 Red
10705 White	10706 Yellow	10707 Orange	10709 Light Green
10710 Metallic Silver	10711 Pink	10712 Violet	10713 Light Blue
10714 Metallic Gold	10715 Brown	10300 Replacement Tip	

- Style: Valve Activated
- Tip Type: Reversible 3 mm bullet/5 mm chisel
- Barrel Material: Aluminum
- Fill quantity: 13 ml
- Marking Width: 3 mm (0.018") – 5 mm (0.196")
- Dimensions*: 5.63" L x 0.63" Ø (142 x 16 mm) *taken w/ marker capped
- Marking Temp. Range: -50° to 150° Fahrenheit (-45° C to 65° C)
- Dry Time: approx. 20 sec.
- Quantity/ Weight Per Box**: 12 ea./ 0.9 lb. (415 g) **other packaging options available
- Quantity/ Weight Per Case: 144 ea./ 11 lb. (5 kg)
- Directions For Use: Shake vigorously with cap on. Press tip until inked. Replace cap after use

PRODUCT FEATURES

- 30% more paint for large marking jobs.
- Reversible bullet / chisel tip provides more marking options.
- Anti-roll cap with clip is easy to remove and replace.
- Marker fits in U-Holder™.
- Permanent xylene free paint.
- Made in USA.

TYPICAL USES

- General purpose industrial marking for quality assurance, color coding and parts identification.
- Marking of tools, inventory, and work-in-progress.
- Highly visible and permanent on most surfaces such as metals, plastics, wood, glass, ceramics, corrugated cardboard, textiles, etc.

SAFETY INFORMATION

- Read SDS before using (available online at www.umarkers.com).
- Conforms to ASTM D4236.
- Keep out of reach of children. For professional use only.